

## Series 4117

**TUFF FLEX**

**Exceeds SAE 100R17**



Designed as a replacement for standard SAE 100R17 lines, where a more abrasion resistant hose is needed. MSHA flame retardant approved "Tuff-Flex" super high abrasion resistant compound cover. Fabric impression.

<b>Tube:</b>	Type A maximum oil resistant synthetic rubber.
<b>Reinforcement:</b>	One braid of high tensile steel wire.
<b>Cover:</b>	Flame retardant, super high abrasion resistant "Tuff-Flex". MSHA approved.
<b>Temperature:</b>	-40° F. to +212° F. (-40° C. to +100° C.) (+275° F Intermittent) (+135° C)
<b>Branding:</b>	White letters with silver box.

Part #	Inside Diameter		Outside Diameter		W.P. (PSI)	Burst (PSI)	Minimum Bend Rad (In.)	Weight Lbs/Ft	Coupling Series
	(In.)	(MM)	(In.)	(MM)					
4117-04	1/4	6.4	0.48	12.2	3040	12,160	2.0	0.12	KW
4117-06	3/8	9.5	0.61	15.5	3040	12,160	2.6	0.19	KW
4117-08	1/2	12.7	0.75	19.1	3040	12,160	3.5	0.24	KW

**Note: Series 5117 with "Armor-Clad" super long-life cover is available upon request.**