

## Series 4216

**TUFF FLEX**

**Exceeds SAE 100R16  
EN857 Type 2SC**



Designed as a replacement for standard SAE 100R16 lines, where a more abrasion resistant hose is needed. MSHA flame retardant approved "Tuff-Flex" super high abrasion resistant compound cover. Fabric impression.

<b>Tube:</b>	Type A maximum oil resistant synthetic rubber.
<b>Reinforcement:</b>	Two braids of high tensile steel wire.
<b>Cover:</b>	Flame retardant, super high abrasion resistant "Tuff-Flex". MSHA approved.
<b>Temperature:</b>	-40° F. to +212° F. (-40° C. to +100° C.) (+257 ° F Intermittent) (+125 ° C)
<b>Branding:</b>	White letters with green box.

Part #	Inside Diameter		Outside Diameter		W.P. (PSI)	Burst (PSI)	Minimum Bend Rad (In.)	Weight Lbs/Ft	Coupling Series
	(In.)	(MM)	(In.)	(MM)					
4216-04	1/4	6.4	0.53	13.5	5800	23,200	3.0	0.20	KW
4216-06	3/8	9.5	0.67	17.0	5000	20,000	3.5	0.29	KW
4216-08	1/2	12.7	0.82	20.8	4000	16,000	5.1	0.39	KW
4216-10	5/8	15.9	0.94	23.9	3625	14,500	6.7	0.47	KW
4216-12	3/4	19.1	1.10	30.5	3120	12,480	7.9	0.55	KW
4216-16	1	25.4	1.40	35.6	3000	12,000	9.8	0.80	KW

**Note: Series 5216 with "Armor-Clad" super long-life cover is available upon request.**