

Series 4400

TUFF FLEX

SAE 100R4

High-Temp Suction/Return Line



Specially designed for suction or return line applications where resistance to high temperature is required. Meets or exceeds requirements of SAE 100R4, has half the bend radius of standard 100R4 and the cover meets MSHA 2G. Made in the USA.

Tube:	Black Nitrile.
Reinforcement:	Multiple textile plies with dual wire helix.
Cover:	Black Neoprene. Fabric impression.
Temperature:	-40° F. to +275° F. (-40° C. to +135° C.) +300° F. Intermittent (+149° C. Intermittent)
Branding:	White letters with red box.

Part #	Inside Diameter		Outside Diameter		W.P. (PSI)	Burst (PSI)	Minimum Bend Rad (In.)	Weight Lbs/Ft	Coupling Series
	(In.)	(MM)	(In.)	(MM)					
4400-12	3/4	19.1	1.22	31.0	300	1,200	2.5	0.45	KW/PW/SH
4400-16	1	25.4	1.45	36.8	250	1,000	3.0	0.54	KW/PW/SH
4400-20	1-1/4	31.8	1.76	44.7	200	800	4.0	0.77	KW/PW/SH
4400-24	1-1/2	38.1	2.01	51.1	150	600	5.0	0.91	PW/SH
4400-32	2	50.8	2.51	63.7	100	400	6.0	1.16	PW/SH